

# Compact Slitting Unit

## Greater efficiency and flexibility in slitting

Stand-alone slitting unit that integrates into any rotary press. Circular or blade knife, cutting or perforating, and down to 10 mm between cuts.



### 10 mm

MINIMUM DISTANCE BETWEEN CUTS

#### Depth with a single knob

The adjustment knob varies the contact pressure of the knife's rotary holder, and with it the cutting depth.

### Two knives

CIRCULAR OR BLADE

#### Positioned to the millimetre

Once in place, the fine-thread spindle finishes adjusting the cutter crosswise, to set the cut at the right web width.

### Cut or perforation

LENGTHWISE, YOUR CHOICE

#### Very close cuts

The design has been refined to achieve the smallest possible distance between cuts: 10 mm.

## TWO SYSTEMS

## Circular knife or blade knife



Spare knives and holders are both available

## ADVANTAGES

## What it brings to the line

01

### Full integration

It fits into any production line, on an existing structure or on a new, adapted one.

02

### Cut control

The adjustments make it easy to change the position and depth of the cut.

03

### Easy maintenance

The knives are replaced quickly when they wear.

04

### Optimised design

Refined to guarantee the smallest possible distance between cuts: 10 mm.

## NEXT STEP

## How many cuts do you need?

Tell us the web width, the material and the distance between cuts. We will tell you how many units you need and with which knife.

TECNOCUT · BARCELONA

Rambla Solanes, 21  
08940 Cornellà de Llobregat  
+34 93 261 05 83  
[tecnocut@tecnocut.com](mailto:tecnocut@tecnocut.com)  
[www.tecnocut.com](http://www.tecnocut.com)